

## DS-2CD2322WD-I 2MP WDR EXIR Turret Network Camera



- Up to 2 megapixel high resolution
- Full HD1080p video
- Dual stream
- 2.8mm/4mm/6mm fixed lens
- 120dB Wide Dynamic Range
- 3D Digital Noise Reduction
- Backlight Compensation
- DC12V & PoE
- Support H.264+
- High performance EXIR LED
- Up to 30m IR range
- IP67 weather-proof protection
- 3-axis adjustment
- Dual stream
- Mobile Monitoring via EZVIZ P2P or Hik-Connect

### Camera Accessories



Wall Mount  
DS-1273ZJ-130-TRL



Junction Box  
DS-1280ZJ-M



Inclined Ceiling Mount  
DS-1281ZJ-M



Corner mount  
DS-1276ZJ



Vertical Pole mount  
DS-1275ZJ



# DS-2CD2322WD-I 2MP WDR EXIR Turret Network Camera



## Specification

<b>Camera</b>	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	0.01Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Lens	2.8mm, 4mm, 6mm @ F2.0 angle of view: 114°(2.8mm), 88°(4mm), 55°(6mm)
Lens Mount	M12
Day &Night	IR cut filter with auto switch
DNR	3D DNR
Wide Dynamic Range	120dB
Angle Adjustment	Pan:0° ~ 360°, Tilt: 0° ~ 75°, Rotation: 0° ~ 360°
<b>Compression</b>	
Video	H.264 / MJPEG/H.264+
H.264 Type	Main Profile
Video Bit Rate	32 Kbps ~ 16 Mbps
Dual streams	Support
<b>Image</b>	
Max. Resolution	1920 × 1080
Max Frame Rate	50Hz: Main stream:25fps(1920×1080),25fps(1280×960),25fps(1280×720) Sub stream:25fps(352×288),25fps(640×360) 60Hz: Main stream:30fps (1920×1080), 30fps(1280×960), 30fps(1280×720) Sub stream: 30fps(352×240),30fps(640×360)
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
BLC	Support, zone configurable
ROI Codec	Support
<b>Network</b>	
Network Storage	NAS (Support NFS,SMB/CIFS), ANR
Detection	Intrusion detection, Line crossing detection, Motion detection, Dynamic analysis
Face Detection	Detects the face appears in the surveillance scene and triggers linkage methods such as alarm info and email info
Alarm Trigger	Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
General Function	Anti-Flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access
Standard	ONVIF (PROFILE S, PROFILE G),ISAPI
<b>Interface</b>	
Communication Interface	1 RJ45 10M/100M Ethernet port

# DS-2CD2322WD-I 2MP WDR EXIR Turret Network Camera



## General

Operating Conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F), Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 25%, PoE (802.3af)
Power Consumption	Max. 5.5W (Max. 7.5W with ICR on)
Material	Housing: Plastic; Body & Dome Cover: Metal
IR Range	Approx. 30 meters
Ingress Protection	IP67
Dimensions	Φ127×97.5 (5.0" × 3.8")
Weight	670g (1.5 lbs)

## Order Models

DS-2CD2322WD-I

## Dimensions

